

**VICTOR 6243+ 3 1/2 Digital Meter**

- New type holster, streamline design.
- Large LCD makes the reading clearly.
- Metallic screen board with stronger antimagnetic and anti-interferential function.
- Buzzer alarm, data hold, Diode and Transistor test function.

Inductance(L)	VICTOR 6243+ Capacitance/Resistance/Inductance		
Range	Accuracy	Resolution	Measuring frequency
2mH	±(2.0%+5d)	1uH	Approx:200Hz
20mH		10uH	
200mH		100uH	
2H	±(5.0%+5d)	1mH	
20H	±(5.0%+15d)	10mH	

Range	Accuracy	Resolution	Measuring frequency
2nF	±(1.0%+5d)	1pF	Approx:200Hz
20 nF		10 pF	
200 nF		100 pF	
2uF	±(2.0%+5d)	1 pF	
20 uF	±(5.0%+5d)	10 pF	Approx:16Hz
200 uF		100 pF	
1000 uF		±(5.0%+25d)	1 pF

Range	Accuracy	Resolution
200Ω	± (0.8%+5d)	0.1Ω
2kΩ	±(0.8%+3d)	1Ω
20kΩ		10Ω
200kΩ		100Ω
2MΩ		1kΩ
20MΩ	±(1.0%+15d)	10kΩ