



MA882/MA883/MA884/MA885 Digital Refractometers for Grape Juice Must Measurements

The **MA882**, **MA883**, **MA884** and **MA885** are optical instruments that are based on the measurement of the refractive index of a solution. The measurement of refractive index is simple and quick and provides the vintner an accepted method for sugar content analysis. Samples are measured after a simple user calibration with deionized or distilled water. Within seconds the instrument measures the refractive index of the grape. This digital refractometers eliminate the uncertainty associated with mechanical refractometers and are easily portable for measurements in the field.

The four instruments utilize internationally recognized references for unit conversion and temperature compensation.

Temperature (in °C or °F) is displayed simultaneously with the measurement on the large dual level display along with icons for Low Power and other helpful message codes.

Key features include:

- Dual-level LCD
- Easy setup and storage
- Automatic Temperature Compensation (ATC)
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

- **MA882** measures %Brix;
- **MA883** measures °Baumé;
- **MA884** measures %Brix and Potential Alcohol (% vol);
- **MA885** measures %Brix, °Oechsle (°Oe) and °KMW (°Babo).

Specifications	 MA882	 MA883	 MA884	 MA885
Range	0 to 50% Brix 0 to 80°C / 32 to 176°F	0 to 28 °Baumé 0 to 80°C / 32 to 176°F	0 to 50% Brix 0 to 25% v/v Potential Alc. 0 to 80°C / 32 to 176°F	0 to 50% Brix 0 to 230 °Oechsle 0 to 42 °KMW 0 to 80°C / 32 to 176°F
Resolution	0.1% Brix 0.1°C / 0.1°F	0.1 °Baumé 0.1°C / 0.1°F	0.1% Brix 0.1% v/v Potential Alcohol 0.1°C / 0.1°F	0.1% Brix 0.1 °Oechsle 0.1 °KMW 0.1°C / 0.1°F
Accuracy	±0.2% Brix ±0.3°C / ±0.5°F	±0.1 °Baumé ±0.3°C / ±0.5°F	±0.2% Brix ±0.2 v/v Potential Alcohol ±0.3°C / ±0.5°F	±0.2% Brix ±1 °Oechsle ±0.2 °KMW ±0.3°C / ±0.5°F
Light Source	yellow LED	yellow LED	yellow LED	yellow LED
Measurement Time	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F
Case Material	ABS	ABS	ABS	ABS
Battery Type	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)
Battery Life	5000 reading	5000 reading	5000 reading	5000 reading
Auto-shut off	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	660 g	660 g	660 g	660 g

Ordering Information

MA882, **MA883**, **MA884** and **MA885** are supplied in a carton box, complete with 9V battery, pipette and instruction manual.

Optionally you can also order the refractometers in a hard carrying case (**MA752**).

