

USB CABLE DATALOGGER



88394



88195



88193

88393

88396

Temperature Datalogger (Interface: Cable) w/LCD:88195, 88394, 88397 w/o LCD:88193, 88393, 88396

- Display & record real time temperature
- 2 ways to program & download data:
 - 1) via PC: USB cable
 - 2) via logger printer 9801: 9801 is a 3 function in 1 printer for programing & download
- Yellow LED: recording indicator ; Red LED flash while exceeding threshold
- Several methods to start recording:
 - 88395:button/schedule /immediately/repeat/on line
 - 88398:magnet/schedule/immediately/repeat/on line



Metric/Imperial



Low Battery



Auto Logging



PC Link




USB 1.0



LED Alarm



IP65



Model	88195 88193	88394 88393	88397 88396
Air temp. range	-30~70°C	-40~85°C	-40~85°C
Air temp. resolution	0.1°C/°F		
Air temp. accuracy	+/-0.6°C (-20~50°C), others +/-1.2°C		
External temp. range	N/A	-40~100°C	-40~100°C
External temp. Accuracy	N/A	+/-0.6°C (-20~50°C), others +/-1.2°C	
Sampling points	88195:8000 88193:4000	16000	16000
Button to on/off	YES	YES	N/A
Battery life time	>6 MONTHS		
LCD size (mm, HxW)	w/LCD:88195, 88394, 88397 --> 13*33 w/o LCD:88193, 88393, 88396 -->N/A		
Logger activation	- 88195:button/schedule /immediately start - 88394:button/schedule /immediately/repeat/on line - 88397:magnet/schedule/immediately/repeat/on line - 88193:button/schedule /immediately start - 88393:button/ schedule /immediately/repeat/on line - 88396:magnetic/schedule/immediately/repeat/on line		
Operating temp.	0~50°C		
Operating RH%	Humidity < 80%		
Storage temp.	-20~50°C		
Storage RH%	Humidity < 90%		
Dimension(mm,LxWxT)	75.5X53X23.5		
Weight	~70g		
Battery	CR2 X 1PC		
Standard Package	Meter/Battery/Manual/Paper box		
Optional Accessory	External probe / Software kit /9801 printer		

Ordering Code

VZ88195AZ, 88195 logger
 VZ88193AZ, 88193 logger
 VZ88393AZ, 88393 logger
 VZ88394AZ, 88394 logger
 VZ88396AZ, 88396 logger
 VZ88397AZ, 88397 logger
 VZ87P6AZ, Thermistor probe
 VZUSBAZD, Logger PC kit
 VZ9801AZ, Printer set

Optional



EXTERNAL TEMP. PROBE
 P/N: VZ87P6AZ
 For 88395/398
 Color: black
 Size: 15cm probe w/handle
 Cable: 116cm w/2.5mm jack



USB CABLE
 P/N:VZUSBAZD
 USB 1.0 interface
 Size : cable 125cm
 USB connector to pc
 -2.5mm dia. Stereo phone
 Jack to logger