



Specification

	Transmitter	Receiver
Dimension	64*31*119mm	48.6*26*177mm
Power	1.5V AAA*3batteries	6F22 9V battery
Weight	119.2g	68.8g
Signal Tracing Transmit Distance	>1km	
Display	LED	
Operating Temperature	-10 ~40°C (14 ~ 104°F)	
Operating Humidity	10-95%	
Storage Temperature	-20 ~ 60°C (-4~140°F)	

Features

1. Long distance wiring tracing.
2. Internet cable order verifying .
3. Wiring voltage existence inspection.
4. Wiring voltage positive or negative characteristic measuring.
5. Wiring shorts inspection.
6. Low battery indication.
7. Tracing sensitiveness and volume adjusting.
8. Headphone jack output.
9. Flashlight.

Name Of The Components

- | | |
|---|------------------------------|
| a. RJ45 interface | b. RJ11 interface |
| c. Function indication light | d. Housing |
| e. Signal tracing sensor | f. Flashlight |
| g. Operation indication light | h. Headphone jack |
| i. Volume control wheel | j. Scan cable tracing button |
| k. Flashlight switch | |
| l. Cable order verifying lights section | |
| m. RJ45 cable order verifying socket | |
| n. Audio output | o. Battery door |

Buttons

- (1) Power: power button
- (2) V: Voltage testing button
- (3) Ω: Cable shorts, opens inspection
- (4) TEST FAST: Fast cable order verifying button
- (5) TEST SLOW: Slow cable order verifying button
- (6) SCAN FAST: Fast tracing frequency button
- (7) SCAN NOR.: Normal tracing frequency button
- (8) SCAN SLOW: Slow tracing frequency button

