



[Enlarge](#)



[Download Manual](#)

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/600V	$\pm(0.8\%+1)$
AC Voltage	4V/40V/400V/600V	$\pm(1\%+5)$
DC Current	40A/400A	$\pm(2\%+3)$
AC Current	40A/400A	$\pm(2.5\%+5)$
Resistance	400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω	$\pm(1\%+2)$
Frequency	10Hz~1MHz	$\pm(0.1\%+3)$
Duty Cycle	0.1%~99.9%	✓
Special Functions		
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
Full Icon Display		✓
Sleep Mode		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10M Ω	✓
Max. Display	3999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	35.6 x 18 mm
Product Colour	Red and Grey
Product Net Weight	200g
Product Size	210 x 75.6 x 30mm
Standard Accessories	Test Lead, English Manual, Carrying Bag
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	510 x 490 x 330mm (0.082 CBM Per Standard Carton)
Standard Carton Gross Weight	15kg

[Back to main menu](#)