

SIMATIC S7-1200, CPU 1211C, compact CPU, AC/DC/relay,  
onboard I/O: 6 DI 24 V DC; 4 DO relay 2A; 2 AI 0-10 V DC, Power  
supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 50 KB



| General information                 |                                       |
|-------------------------------------|---------------------------------------|
| Product type designation            | CPU 1211C AC/DC/relay                 |
| Firmware version                    | V4.2                                  |
| Engineering with                    |                                       |
| • Programming package               | STEP 7 V14 or higher                  |
| Supply voltage                      |                                       |
| Rated value (AC)                    |                                       |
| • 120 V AC                          | Yes                                   |
| • 230 V AC                          | Yes                                   |
| permissible range, lower limit (AC) | 85 V                                  |
| permissible range, upper limit (AC) | 264 V                                 |
| Line frequency                      |                                       |
| • permissible range, lower limit    | 47 Hz                                 |
| • permissible range, upper limit    | 63 Hz                                 |
| Input current                       |                                       |
| Current consumption (rated value)   | 60 mA at 120 V AC; 30 mA at 240 V AC  |
| Current consumption, max.           | 180 mA at 120 V AC; 90 mA at 240 V AC |
| Inrush current, max.                | 20 A; at 264 V                        |

|   |   |
|---|---|
| $I^2t$  | 0.8 A <sup>2</sup> ·s   |
| <b>Output current</b>                                     |   |
| for backplane bus (5 V DC), max.                          | 750 mA; Max. 5 V DC for CM  |
| <b>Encoder supply</b>                                     |   |
| 24 V encoder supply                                       |   |
| • 24 V  | 20.4 to 28.8V   |
| <b>Power loss</b>   |   |
| Power loss, typ.  | 10 W  |
| <b>Memory</b>   |   |
| Work memory   |   |
| • integrated  | 50 kbyte  |
| • expandable  | No  |
| Load memory   |   |
| • integrated  | 1 Mbyte   |
| • Plug-in (SIMATIC Memory Card), max.                     | with SIMATIC memory card  |
| Backup  |   |
| • present   | Yes   |
| • maintenance-free  | Yes   |
| • without battery   | Yes   |
| <b>CPU processing times</b>                               |   |
| for bit operations, typ.                                  | 0.08 µs; / instruction  |
| for word operations, typ.                                 | 1.7 µs; / instruction   |
| for floating point arithmetic, typ.                       | 2.3 µs; / instruction   |
| <b>CPU-blocks</b>   |   |
| Number of blocks (total)                                  | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB  |   |
| • Number, max.  | Limited only by RAM for code  |
| <b>Data areas and their retentivity</b>                   |   |
| Retentive data area (incl. timers, counters, flags), max. | 10 kbyte  |
| Flag  |   |
| • Number, max.  | 4 kbyte; Size of bit memory address area  |
| Local data  |   |
| • per priority class, max.                                | 16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB   |
| <b>Address area</b>                                       |   |
| Process image   |   |
| • Inputs, adjustable                                      | 1 kbyte   |

|   |  |
|---|--|
| • Outputs, adjustable                                 | 1 kbyte  |
| <b>Hardware configuration</b>                         |  |
| Number of modules per system, max.                    | 3 communication modules, 1 signal board  |
| <b>Time of day</b>                                    |  |
| <b>Clock</b>  |  |
| • Hardware clock (real-time)                          | Yes  |
| • Backup time   | 480 h; Typical   |
| • Deviation per day, max.                             | ±60 s/month at 25 °C   |
| <b>Digital inputs</b>                                 |  |
| Number of digital inputs                              | 6; Integrated  |
| • of which inputs usable for technological functions  | 3; HSC (High Speed Counting)   |
| Source/sink input                                     | Yes  |
| <b>Number of simultaneously controllable inputs</b>   |  |
| all mounting positions                                |  |
| — up to 40 °C, max.                                   | 6  |
| <b>Input voltage</b>                                  |  |
| • Rated value (DC)                                    | 24 V   |
| • for signal "0"                                      | 5 V DC at 1 mA   |
| • for signal "1"                                      | 15 V DC at 2.5 mA  |
| <b>Input current</b>                                  |  |
| • for signal "1", typ.                                | 4 mA; nominal  |
| <b>Input delay (for rated value of input voltage)</b> |  |
| for standard inputs                                   |  |
| — parameterizable                                     | 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four |
| — at "0" to "1", min.                                 | 0.2 ms   |
| — at "0" to "1", max.                                 | 12.8 ms  |
| for interrupt inputs                                  |  |
| — parameterizable                                     | Yes  |
| for technological functions                           |  |
| — parameterizable                                     | Single phase : 3 @ 100 kHz, differential: 3 @ 80 kHz                                     |
| <b>Cable length</b>                                   |  |
| • shielded, max.                                      | 500 m; 50 m for technological functions  |
| • unshielded, max.                                    | 300 m; For technological functions: No   |
| <b>Digital outputs</b>                                |  |
| Number of digital outputs                             | 4; Relays  |
| <b>Switching capacity of the outputs</b>              |  |
| • with resistive load, max.                           | 2 A  |
| • on lamp load, max.                                  | 30 W with DC, 200 W with AC  |
| <b>Output delay with resistive load</b>               |  |

|  |  |
|--|--|
| • "0" to "1", max.                                     | 10 ms; max.  |
| • "1" to "0", max.                                     | 10 ms; max.  |
| Relay outputs  |  |
| • Number of relay outputs                              | 4  |
| • Number of operating cycles, max.                     | mechanically 10 million, at rated load voltage 100 000 |
| Cable length   |  |
| • shielded, max.                                       | 500 m  |
| • unshielded, max.                                     | 150 m  |
| Analog inputs  |  |
| Number of analog inputs                                | 2  |
| Input ranges   |  |
| • Voltage  | Yes  |
| Input ranges (rated values), voltages                  |  |
| • 0 to +10 V   | Yes  |
| • Input resistance (0 to 10 V)                         | ≥100k ohms   |
| Cable length   |  |
| • shielded, max.                                       | 100 m; twisted and shielded                            |
| Analog outputs   |  |
| Number of analog outputs                               | 0  |
| Analog value generation for the inputs                 |  |
| Integration and conversion time/resolution per channel |  |
| • Resolution with overrange (bit including sign), max. | 10 bit   |
| • Integration time, parameterizable                    | Yes  |
| • Conversion time (per channel)                        | 625 µs   |
| Encoder  |  |
| Connectable encoders                                   |  |
| • 2-wire sensor  | Yes  |
| 1. Interface   |  |
| Interface type   | PROFINET   |
| Physics  | Ethernet   |
| Isolated   | Yes  |
| automatic detection of transmission rate               | Yes  |
| Autonegotiation  | Yes  |
| Autocrossing   | Yes  |
| Interface types  |  |
| • Number of ports                                      | 1  |
| • integrated switch                                    | No   |
| Protocols  |  |
| • PROFINET IO Controller                               | Yes  |

|   |   |
|---|---|
| • PROFINET IO Device  | Yes   |
| • SIMATIC communication   | Yes   |
| • Open IE communication   | Yes   |
| • Web server  | Yes   |
| • Media redundancy  | No  |
| <b>PROFINET IO Controller</b>   |   |
| • Transmission rate, max.   | 100 Mbit/s  |
| <b>Services</b>   |   |
| — PG/OP communication   | Yes   |
| — S7 routing  | Yes   |
| — Isochronous mode  | No  |
| — Open IE communication   | Yes   |
| — IRT   | No  |
| — MRP   | No  |
| — MRPD  | No  |
| — PROFINergy  | No  |
| — Prioritized startup   | Yes   |
| — Number of IO devices with prioritized startup, max.                         | 16  |
| — Number of connectable IO Devices, max.                                      | 16  |
| — Number of connectable IO Devices for RT, max.                               | 16  |
| — of which in line, max.  | 16  |
| — Activation/deactivation of IO Devices                                       | Yes   |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8   |
| — Updating time   | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |
| <b>PROFINET IO Device</b>   |   |
| <b>Services</b>   |   |
| — PG/OP communication   | Yes   |
| — S7 routing  | Yes   |
| — Isochronous mode  | No  |
| — Open IE communication   | Yes   |
| — IRT   | No  |
| — MRP   | No  |
| — MRPD  | No  |
| — PROFINergy  | Yes   |
| — Shared device   | Yes   |
| — Number of IO Controllers with shared device, max.                           | 2   |

|   |  |
|---|--|
| Protocols   |  |
| Supports protocol for PROFINET IO                 | Yes  |
| PROFIBUS  | Yes; CM 1243-5 required  |
| AS-Interface                                      | Yes; CM 1243-2 required  |
| Protocols (Ethernet)                              |  |
| • TCP/IP  | Yes  |
| • DHCP  | No   |
| • SNMP  | Yes  |
| • DCP   | Yes  |
| • LLDP  | Yes  |
| Open IE communication                             |  |
| • TCP/IP  | Yes  |
| — Data length, max.                               | 8 kbyte  |
| — several passive connections per port, supported | Yes  |
| • ISO-on-TCP (RFC1006)                            | Yes  |
| — Data length, max.                               | 8 kbyte  |
| • UDP   | Yes  |
| — Data length, max.                               | 1 472 byte   |
| Web server  |  |
| • supported                                       | Yes  |
| • User-defined websites                           | Yes  |
| Further protocols                                 |  |
| • MODBUS  | Yes  |
| Communication functions                           |  |
| S7 communication                                  |  |
| • supported                                       | Yes  |
| • as server                                       | Yes  |
| • as client                                       | Yes  |
| • User data per job, max.                         | See online help (S7 communication, user data size)                   |
| Number of connections                             |  |
| • overall   | 16; dynamically  |
| Test commissioning functions                      |  |
| Status/control                                    |  |
| • Status/control variable                         | Yes  |
| • Variables                                       | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| Forcing   |  |
| • Forcing   | Yes  |
| Diagnostic buffer                                 |  |
| • present   | Yes  |

|  |                      |
|--|----------------------|
| <b>Traces</b>  |                      |
| • Number of configurable Traces  | 2                    |
| • Memory size per trace, max.  | 512 kbyte            |
| <b>Interrupts/diagnostics/status information</b>   |                      |
| <b>Diagnostics indication LED</b>  |                      |
| • RUN/STOP LED   | Yes                  |
| • ERROR LED  | Yes                  |
| • MAINT LED  | Yes                  |
| <b>Integrated Functions</b>  |                      |
| Number of counters   | 3                    |
| Counting frequency (counter) max.  | 100 kHz              |
| Frequency measurement  | Yes                  |
| controlled positioning   | Yes                  |
| Number of position-controlled positioning axes, max.   | 8                    |
| Number of positioning axes via pulse-direction interface   | Up to 4 with SB 1222 |
| PID controller   | Yes                  |
| Number of alarm inputs   | 4                    |
| <b>Potential separation</b>  |                      |
| <b>Potential separation digital inputs</b>   |                      |
| • Potential separation digital inputs  | 500V AC for 1 minute |
| • between the channels, in groups of   | 1                    |
| <b>Potential separation digital outputs</b>  |                      |
| • Potential separation digital outputs   | Relays               |
| • between the channels   | No                   |
| • between the channels, in groups of   | 1                    |
| <b>EMC</b>   |                      |
| <b>Interference immunity against discharge of static electricity</b>                                 |                      |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2                | Yes                  |
| — Test voltage at air discharge  | 8 kV                 |
| — Test voltage at contact discharge  | 6 kV                 |
| <b>Interference immunity to cable-borne interference</b>   |                      |
| • Interference immunity on supply lines acc. to IEC 61000-4-4  | Yes                  |
| • Interference immunity on signal cables acc. to IEC 61000-4-4                                       | Yes                  |
| <b>Interference immunity against voltage surge</b>   |                      |
| • on the supply lines acc. to IEC 61000-4-5  | Yes                  |
| <b>Interference immunity against conducted variable disturbance induced by high-frequency fields</b> |                      |

|  |  |
|--|--|
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 | Yes  |
| Emission of radio interference acc. to EN 55 011                               |  |
| • Limit class A, for use in industrial areas                                   | Yes; Group 1   |
| • Limit class B, for use in residential areas                                  | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011 |
| Degree and class of protection   |  |
| Degree of protection acc. to EN 60529  |  |
| • IP20   | Yes  |
| Standards, approvals, certificates   |  |
| CE mark  | Yes  |
| UL approval  | Yes  |
| cULus  | Yes  |
| FM approval  | Yes  |
| RCM (formerly C-TICK)  | Yes  |
| KC approval  | Yes  |
| Marine approval  | Yes  |
| Ambient conditions   |  |
| Free fall  |  |
| • Fall height, max.  | 0.3 m; five times, in product package  |
| Ambient temperature during operation   |  |
| • min.   | -20 °C   |
| • max.   | 60 °C  |
| • horizontal installation, min.  | -20 °C   |
| • horizontal installation, max.  | 60 °C  |
| • vertical installation, min.  | -20 °C   |
| • vertical installation, max.  | 50 °C  |
| Ambient temperature during storage/transportation                              |  |
| • min.   | -40 °C   |
| • max.   | 70 °C  |
| Air pressure acc. to IEC 60068-2-13  |  |
| • Operation, min.  | 795 hPa  |
| • Operation, max.  | 1 080 hPa  |
| • Storage/transport, min.  | 660 hPa  |
| • Storage/transport, max.  | 1 080 hPa  |
| Altitude during operation relating to sea level                                |  |
| • Installation altitude, min.  | -1 000 m   |
| • Installation altitude, max.  | 2 000 m  |
| Relative humidity  |  |
| • Operation, max.  | 95 %; no condensation  |
| Vibrations   |  |



|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• Vibration resistance during operation acc. to IEC 60068-2-6</li> </ul> | 2 g (m/s <sup>2</sup> ) wall mounting, 1 g (m/s <sup>2</sup> ) DIN rail                   |
| <ul style="list-style-type: none"> <li>• Operation, tested according to IEC 60068-2-6</li> </ul>                | Yes   |
| <b>Shock testing</b>  |   |
| <ul style="list-style-type: none"> <li>• tested according to IEC 60068-2-27</li> </ul>                          | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms |
| <b>Pollutant concentrations</b>   |   |
| <ul style="list-style-type: none"> <li>• SO<sub>2</sub> at RH &lt; 60% without condensation</li> </ul>          | SO <sub>2</sub> : < 0.5 ppm; H <sub>2</sub> S: < 0.1 ppm; RH < 60% condensation-free      |
| <b>Configuration</b>  |   |
| <b>Programming</b>  |   |
| <b>Programming language</b>   |   |
| — LAD   | Yes   |
| — FBD   | Yes   |
| — SCL   | Yes   |
| <b>Know-how protection</b>  |   |
| <ul style="list-style-type: none"> <li>• User program protection/password protection</li> </ul>                 | Yes   |
| <ul style="list-style-type: none"> <li>• Copy protection</li> </ul>   | Yes   |
| <ul style="list-style-type: none"> <li>• Block protection</li> </ul>  | Yes   |
| <b>Access protection</b>  |   |
| <ul style="list-style-type: none"> <li>• Protection level: Write protection</li> </ul>                          | Yes   |
| <ul style="list-style-type: none"> <li>• Protection level: Read/write protection</li> </ul>                     | Yes   |
| <ul style="list-style-type: none"> <li>• Protection level: Complete protection</li> </ul>                       | Yes   |
| <b>Cycle time monitoring</b>  |   |
| <ul style="list-style-type: none"> <li>• adjustable</li> </ul>  | Yes   |
| <b>Dimensions</b>   |   |
| Width   | 90 mm   |
| Height  | 100 mm  |
| Depth   | 75 mm   |
| <b>Weights</b>  |   |
| Weight, approx.   | 420 g   |
| <b>last modified:</b>   | 04/18/2019  |