



Optional



RUBBER HOLSTER / STAND
 P/N: VM68601HA, BLUE COLOR
 P/N: VM68601HS+VM68601HS1
 RED COLOR
 P/N: VM68601HS11+VM68601HSA
 GREY COLOR

Ordering Code

VZ8851AZ, 8851 Thermometer
VZ8852AZ, 8852 Thermometer
VZ8855AZ, 8855 Thermometer
VZ8856AZ, 8856 Thermometer
VE60A000, 1 METER LONG bead K
VE60A0YK, 4 METERS LONG bead K
VZUSBAZM, USB software kit

Thermocouple Thermometer w/PC Link 8851/8852/8855/8856

- Fashion design and the most popular & fast multiple type thermocouple measuring meter
- Super big LCD for easy reading
- Data records stamped with real time clock
- Features of each model:
 8851: single input &K/J/T probe compatible
 8852: dual input &K/J/T probe compatible
 8855: single input &K/J/T/R/S/E probe compatible
 8856: dual input &K/J/T/R/S/E probe compatible



Model	8851	8852	8855	8856
K temp. Range & Accuracy (under 18~28°C ambient temp.)			-200~1370°C ; ±(0.1% rdg +0.7°C) -328~2498°F ; ±(0.1% rdg +1.4°F)	
Resolution	-200~650°C/640~1370°C -328~1000°F/990~2498°F		0.1°C/1°C 0.1°F/1°F	
J temp. Range & Accuracy (under 18~28°C ambient temp.)			-200~760°C ; ±(0.1% rdg +0.7°C) -328~1400°F ; ±(0.1% rdg +1.4°F)	
Resolution	-200~500°C/490~760°C -328~940°F/930~1400°F		0.1°C/1°C 0.1°F/1°F	
T temp. Range & Accuracy (under 18~28°C ambient temp.)			-200~390°C ; ±(0.1% rdg +0.7°C) -328~730°F ; ±(0.1% rdg +1.4°F)	
Resolution	-200~390°C -328~730°F		0.1°C 0.1°F	
R temp. Range & Accuracy (under 18~28°C ambient temp.)		N/A	0~1760°C ; ±(0.3% rdg +0.7°C) 32~3200°F ; ±(0.3% rdg +1.4°F)	
Resolution	0~1000°C/990~1760°C 32~1000°F/990~3200°F	N/A	0.1°C/1°C 0.1°F/1°F	
S temp. Range & Accuracy (under 18~28°C ambient temp.)		N/A	0~1760°C ; ±(0.3% rdg +0.7°C) 32~3200°F ; ±(0.3% rdg +1.4°F)	
Resolution	0~1000°C/990~1760°C 32~1000°F/990~3200°F	N/A	0.1°C/1°C 0.1°F/1°F	
E temp. Range & Accuracy (under 18~28°C ambient temp.)		N/A	-200~736°C ; ±(0.1% rdg +0.7°C) -328~1356°F ; ±(0.1% rdg +1.4°F)	
Resolution	-200~404°C/370~736°C -328~760°F/710~1356°F	N/A	0.1°C/1°C 0.1°F/1°F	
LCD size (mm, HxW)	30x51			
Operating temp.	0~50°C			
Operating RH%	Humidity < 80%			
Storage temp.	-20~50°C			
Storage RH%	Humidity < 90%			
Dimension(mm,LxWxT)	182x72x30			
Weight	~150g			
Battery	9V x 1pc or adaptor			
Standard Package	Meter, K bead thermocouple x1, battery, manual.			
Optional Accessory	K type thermocouple (custom made thermocouple is available upon request) Rubber boot			