



EMC & LVD
EN : 61326
EN : 61010-1

Model: DT- 8859

دماسنج لیزری ۱۶۰۰ درجه

قابلیت اندازه گیری :
محدوده اندازه گیری : $-50 \sim 1600\text{ }^{\circ}\text{C}$
دقت اندازه گیری : $\pm 1.0\text{ }^{\circ}\text{C}$
فاصله دستگاه تا نقطه اندازه گیری : 1 : 50

دیگر قابلیت ها :
آلارم قابل تنظیم
چراغ پس زمینه نمایشگر
حافظه مینیم / ماکزیمم / متوسط / میانگین مقادیر
تنظیم ضریب تابش : Emissivity
همراه با کیف حمل

Features

Optical Resolution (D:S)	50:1
High Temperature	1600 °C
User selectable °C or °F	2912 °F
Laser targeting	*
Automatic Data Hold	*
Auto Power Off	*
White Backlit LCD Display	*
Overrange indication	*
Max, Min, DIF, AVG record	*
High / low alarm, Trigger lock	*
Adjustable emissivity	*
150ms faster sampling time with %1 accuracy	

Specifications

Range	- 50 °C to 1600 °C/ - 58 °F to 2912 °F
Response Time	Less than 1 second
Optical Resolution (D:S)	50:1
Resolution	0.1° up to 2000 °, 1° over 2000 °
Basic Accuracy	$\pm 1.5\%$ of reading or $\pm 2\text{ }^{\circ}\text{C}/\pm 4\text{ }^{\circ}\text{F}$
Emissivity	Adjustable 1.0~0.10

Size(HxWxD): 220mm x 120mm x56mm

Weight:290g

Accessories:

9V battery, Carrying case and Gift box.

