

DY8800B

COMBUSTIBLE GAS LEAK DETECTOR

- Audible ticker signal and visual leak size indicator
- Adjustable sensitivity, fast warm-up
- Goose neck probe

CE



SPECIFICATION

DY8800B

Detection	Methane(LNG,CNG), Ethane, Propane, Butane, Acetone, Alcohol, Ammonia, Steam, Gasoline, Jet fuel, Hydrogen Solvents, Lacquer thinner, Naphtha
Sensor	planar semiconductor
Warm up time	<30 seconds
Sensitivity	adjustable, as low as 5ppm(gasoline)
Alarm mode	sound, light
Length of probe	23cm/9"
Working temperature	0°C~50°C
Working humidity	within 90% RH
Dimension	171*43*38mm
Weight	240g
Power source	1.5V AAA*4

STANDARD ACCESSORIES



Heavy duty oxford fabric bag
DY45I

DY5750B

REFRIGERATION GAS LEAK DETECTOR

- Audible ticker signal and visual leak size indicator
- Adjustable sensitivity, fast warm-up
- Goose neck probe

CE



SPECIFICATION

DY5750B

Detection	CFCs: R12, R11, R500, R503 HCFCs: R22, R123, R124, R502 HCFCs: R134a, R404a, R125 SF6, Halogen gases
Warm up time	6s
Sensitivity	adjustable, maximum 14g/yr(0.49oz/yr)
Alarm mode	sound, light
Length of probe	23cm/9"
Working temperature	0°C~50°C
Working humidity	within 90% RH
Dimension	171*43*38mm
Weight	240g
Power source	1.5V AAA*4

STANDARD ACCESSORIES



Heavy duty oxford fabric bag
DY45I