

Specifications	HI96711 Free and Total Chlorine	

	Chlorine, Free (P1)		Chlorine, Total (P2)			
Range	0.00 to 5.00 mg/L (ppm)					
Resolution	0.01 mg/L from 0.00	0.01 mg/L from 0.00 to 3.50 mg/L (ppm); 0.10 mg/L above 3.50 mg/L (ppm)				
Accuracy @25°C (77°F)	±0.03 mg/L ±3% of reading					
Light Source	tungsten lamp					
Light Detector	silicon photoce ll with narrow band interference filter @ 525 nm					
Power Supp l y	9V battery					
Auto-off	after ten minutes of non-use in measurement mode; after one hour of non-use in calibration mode; with last reading reminder					
Environment	0 to 50°C (32 to 122°F); RH max 95% non-condensing					
Dimensions	192 x 104 x 69 mm (7.6 x 4.1 x 2.7")					
Weight	320g (11.3 oz.)					
Method	adaptation of the USEPA method 330.5 and Standard Method 4500-CI G					
Ordering	HI96711 is supplied with sample cuvettes (2) with caps, 9V battery, instrument quality certificate and instruction manual. CAL Check standards and testing reagents sold separately					
Information	HI96711C includes photometer, CAL Check standards, sample cuvettes (2) with caps, 9V battery, scissors, cuvette cleaning cloth, instrument quality certificate, instruction manual and rigid carrying case. Reagents sold separately					
Reagents and Standards	HI96711	HI96701-11	CAL Check standard cuvettes (free CI)			
		HI93701-01	reagents for 100 tests (free Cl)			
		HI93701-03	reagents for 300 tests (free CI)			
		HI96711-11	CAL Check standard cuvettes (total Cl)			
		HI93711-01	reagents for 100 tests (total CI)			
		HI93711-03	reagents for 300 tests (total CI)			

HI96711

Chlorine, Free and Total Portable Photometer

- CAL Check™
 - Allows for performance verification and calibration of the meter using NIST traceable standards
- Auto-shut off
- · Built-in timer
 - Display of time remaining before a measurement is taken

The HI96711 portable photometer is for the measurement of free and total chlorine. Hanna's portable photometers feature an advanced optical system; the combination of a special tungsten lamp, a narrow band interference filter, and silicon photodetector ensure accurate photometric readings every time. The Hanna exclusive CAL Check feature utilizes ready-made, NIST traceable standards to verify both meter validation and calibration. The exclusive cuvette locking system ensures that the cuvette is inserted into the measurement cell in the same position every time to maintain a consistent path length.

Significance of Use

As one of the oldest and most common forms of disinfection, chlorine improves water quality by destroying disease-producing microorganisms and by reacting with other organic and inorganic substances. Chlorine levels must be actively monitored to ensure sufficient chlorine is present for disinfection, as well as to control adverse effects such as taste, odor, and potential reactions with organic matter to form harmful disinfection byproducts.

