

## Technical Data Sheet

Pressure / Temperature / Humidity / Air Velocity / Airflow / Sound level

### Kimo Kigaz 200 STD Combustion Gas Analyzer Kimo Kigaz 200 PRO Combustion Gas Analyzer

CE

## KIGAZ 200 COMBUSTION GAS ANALYSER



Interchangeable O<sub>2</sub>, COH<sub>2</sub>,  
NO et CH<sub>4</sub> sensors



Supplied with magnetic  
protective cover



TÜV-SÜD Approved  
EN50379 - 1&2  
(\$5.5 / \$5.6 / \$5.7)



### KEY POINTS



CO sensor protection by  
solenoid valve



Autozeroing in the flue

- CO sensor protection by solenoid valve
- LED on probe handle to light dark areas
- Single connector

- Step-by-step procedure (gas flow...)
- Integrated printer
- Interchangeable duct
- 2 Go of memory (100 000 measurements)

### INSTRUMENT FEATURES

<b>GAS</b>	- Autozero in the flue - CO sensor protection by solenoid valve	Flue gas CO and ambient CO max	Interchangeable sensors : O <sub>2</sub> and CO-H <sub>2</sub> and NO and CH <sub>4</sub> (optional)	Excess air Losses	Efficiency > 100%
<b>PRESSURE</b>	Differential pressure measurement	Draft measurement			
<b>TEMPERATURE</b>	Ambient temperature	Flue gas temperature	Delta Temperature	DHW temperature 2 thermocouples	Dew point temperature
<b>OTHERS FUNCTIONS</b>	15 programmed combustible <sup>1</sup>	Adding 5 combustibles by the user	Automatic measurement	Opacity index	

<sup>1</sup>Combustibles : Sahara/Fos-sur-Mer Natural Gas, Groningen Natural Gas, Russia/North Sea Natural Gas, Propane, LPG, Butane, Light Oil, Heavy Oil, Bituminous coal, Hard coal, Coke gas, Bio fuel 5%, Wood 20%, Wood-chip 21%, Pellet 8%

## MEASUREMENT RANGES


Parameter	Sensor	Measuring range	Resolution	Accuracy*	T <sub>90</sub> response time
O <sub>2</sub>	Electro-chemical	From 0% to 21%	0.1% vol.	±0.2% vol.	30 s
CO (with H <sub>2</sub> compensation)	Electro-chemical	From 0 to 8000 ppm	1 ppm	From 0 to 200 ppm : ±10 ppm From 201 to 2000 ppm : ±5% of measured value From 2001 to 8000 ppm : ±10% of measured value	30 s
NO	Electro-chemical	From 0 to 5000 ppm	1 ppm	From 0 to 100 ppm : ±5 ppm. From 101 to 5000 ppm : ±5% of measured value	30 s
NO <sub>x</sub>	Calculated**	From 0 to 5155 ppm	1 ppm		
CO <sub>2</sub>	Calculated**	From 0 to 99% vol	0.1% vol		
CH <sub>4</sub>	Semiconductor	From 0 to 10000 ppm From 0 to 1% Vol From 0 to 20 %LEL	1 ppm 0.0001% Vol 0.002%LEL	±20% of full scale	40 s
Flue gas temperature	K thermocouple	From -100 to +1250°C	0.1°C	±1 °C	45 s
Ambient temperature	Internal NTC	From -20 to +120°C	0.1°C	±0.5°C	
Ambient temperature	Pt100 (1/3 Din external probe)	From -50 to +250°C	0.1°C	±0.3% of measured value ±0,25°C	30 s
Dew point temperature	Calculated**	From 0 to +99°Ctd	0.1°C		
DHW temperature	TcK (external probe)	From -200 to +1300 °C	0.1°C	±1 °C	
Differential pressure Draft	Piezoelectric	From -20 000 to +20 000 Pa	1 Pa	From -20 000 to -751 Pa : ±(-0.5% of measured value +4.5 Pa) From 750 to -61 Pa : ±(-0.9% of measured value +1.5 Pa) From -60 to 60 Pa : ±2 Pa From 61 to 750 Pa : ±(0.9% of measured value +1.5 Pa) From 751 to 20 000 Pa : ±(0.5% of measured value + 4.5 Pa)	
Losses	Calculated**	From 0 to 100%	0.1%		
Flue gas velocity		From 0 to 99.9 m/s	0.1 m/s		
Excess air (λ)	Calculated**	From 1 to 9.99	0.01		
Efficiency (η <sub>s</sub> )	Calculated**	From 0 to 100%	0.1 %		
Efficiency (η <sub>t</sub> ) (condensation)	Calculated**	From 0 to 120%	0.1%		
Opacity index	External instrument	From 0 to 9			

\*All accuracies indicated in this document were stated in laboratory conditions and can be guaranteed for measurements carried out in the same conditions, or carried out with required compensation.

\*\*Calculation is made based on the measured values by the analyzer.

## TECHNICAL FEATURES

	Features
Dimensions	Instrument : 331 x 112 x 86 mm Flue gas probe : 300 mm Cable length : 2.50 m
Weight (with battery)	1160 g
Display	Grey scale 3.5" display
Keypad	Rotating button ; 3 function keys + OK key ; Backlighted keypad
Material	Housing and probe : ABS ; Probe cable : neoprene
Protection	IP40
PC interface	Bluetooth® (optional) ; USB
Power supply	Li-Ion battery 3.6 V 4400 mA
Battery life	10 h in continuous operating
Use temperature	From +5 to +50°C
Storage temperature	From -20 to +50°C

**MENUS / ACTIVE VIEWS / APPLICATION**


Analyser menus



Example of analysis



DHW network temperature



Ambient CO checking

**INSTRUMENT DESCRIPTION**
**> Overview**

**> Connections**

 External probes connection  
 (Pt100 temperature, CH<sub>4</sub>...)


Thermocouple connections

Top view

Flue gas connection



P- pressure plug

P+ pressure plug

 Bottom view  
 actoolsupply.com

Power supply connection

USB connection



Right side view

## SUPPLIED WITH


Model	KIGAZ 200 STD	KIGAZ 200 PRO
<b>Supplied with</b>		
Number of interchangeable sensors	2 (O <sub>2</sub> and CO-H <sub>2</sub> )	3 (O <sub>2</sub> , CO-H <sub>2</sub> and NO)
Scalable	yes : NO or CH <sub>4</sub>	Yes : CH <sub>4</sub>
Calibration certificate	yes	yes
Transport bag	yes	yes
Flue gas probe and its water trap	yes	yes
Magnetic protective cover	yes	yes
Differential pressure kit	yes	yes



Transport bag

## SOFTWARE

**Analysers are supplied with LIGAZ software** allowing database creation (Customers, Boilers, inspections), downloading and printing inspections and analyser configuration.



## ACCESSORIES\*

**SCOT** : Ambient CO probe

**SCO2T** : Ambient CO<sub>2</sub> probe

**SPA 150SP** : Ambient Pt100 probe

**SKCL 150** : Thermocouple probe with lamella

**SCI** : Ionisation current measurement probe

**SDFG** : Gas leak detection probe (CH<sub>4</sub>)

**PSK-180** : Flue gas probe with interchangeable contact tip, **180 mm** length, up to **500 °C**

**PSK-300** : Flue gas probe with interchangeable contact tip, **300 mm** length, up to **500 °C**

**PSK-750** : Flue gas probe with interchangeable contact tip in INCONEL, **750 mm** length, use up to **1100 °C**

**PSK-1000** : Flue gas probe with interchangeable contact tip in INCONEL, **1000 mm** length, up to **1100 °C**

**KEG** : Gas network tightness kit

**PMO** : Opacity pump

**Bluetooth® module** : Data downloading and instrument configuration

**LOGAZ** : Software allowing database creation (customers, boilers and inspections), inspections downloading and printing, customizable procedure reports creation, inspection planning, on-site service contracts management (operator planning, customer care) and real-time measurements visualization and recording



Ionisation current probe



Gas leak probe



Gas network tightness kit

\*Please see the technical datasheet of accessories for kigaz for further details