

- Years warranty 2
- ATC
- IP 65
- Points 2
- AUTO Buffer
- Dual Display
- Self diagnosis
- CE
- Electrode Replacement



**pH/EC/TDS/Temp Sensor**

The MW803 MAX and MW804 MAX's exposed temperature sensor provides fast response time, and its proximity to the conductivity probe guarantees much more accurate temperature compensated readings.

**MW803 MAX/MW804 MAX**  
pH/Conductivity/TDS/Temperature Testers  
with replaceable electrode

The MW803 MAX and MW804 MAX are water-resistant testers with dual-level LCD that measure pH/Conductivity/TDS/Temperature in one single tester!

The large display shows readings in an extended range from 0.00 to 14.00 pH and 0 to 3999 µS/cm, 0 to 2000 ppm (MW803), 0 to 20.00 mS/cm, 0 to 10.00 ppt (MW804) and simultaneously shows temperature from 0.0 to 50.0°C or 32.0 to 122.0°F. They have a stability indicator and hold function that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations. The EC/TDS conversion factor is user selectable as well as the temperature compensation coefficient (β).

Ideal for quick and accurate measurements in swimming pools, aquariums and horticultural applications they can also be used in Industrial and Laboratory applications such as cooling towers, food processing, plating, drinking and waste water etc.

Specifications		MW803 MAX	MW804 MAX
Range	pH EC TDS Temp.	0.00 to 14.00 pH 0 to 3999 µS/cm 0 to 2000 ppm 0.0 to 50.0°C / 32.0 to 122.0°F	0.00 to 14.00 pH 0 to 20.00 mS/cm 0 to 10.00 ppt 0.0 to 50.0°C / 32.0 to 122.0°F
Resolution	pH EC TDS Temp.	0.01 pH 1 µS/cm 1 ppm 0.1°C / 0.1°F	0.01 pH 0.01 mS/cm 0.01 ppt 0.1°C / 0.1°F
Accuracy (@25°C)	pH EC/TDS Temp.	±0.05 pH ±2% Full scale ±0.5°C / ±1°F	±0.05 pH ±2% Full scale ±0.5°C / ±1°F
Temperature Compensation		automatic with β=0.0 to 2.4%/°C	automatic with β=0.0 to 2.4%/°C
Calibration		automatic, 1 point for EC and 1 or 2 points for pH	automatic, 1 point for EC and 1 or 2 points for pH
TDS Factor		0.45 to 1.00 (conv.)	0.45 to 1.00 (conv.)
Probe		Mi60P (replaceable)	Mi60P (replaceable)
Environment		0 to 50°C; 100% RH max.	0 to 50°C; 100% RH max.
Battery Type		4 x 1.5V; IEC LR44, A76 (included)	4 x 1.5V; IEC LR44, A76 (included)
Battery Life		approx. 100 hours of use	approx. 100 hours of use
Auto-off		after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions		254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight		220 g	220 g

**Accessories**

- Mi60P** Replaceable probe for MW803 & MW804
- M10000B** Rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- M10016B** Cleaning solution, 20 mL sachet (25 pcs)
- M10030B** 12880 µS/cm calibration solution, 20 mL sachet, 25 pcs
- M10031B** 1413 µS/cm calibration solution, 20 mL sachet, 25 pcs
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet. (25 pcs)

- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL sachet, (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9006** pH 6.86 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9009** pH 9.18 buffer solution, 230 mL bottle
- MA9010** pH 10.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9060** 12880 µS/cm calibration solution, 230 mL bottle
- MA9061** 1413 µS/cm calibration solution, 230 mL bottle
- MA9062** 1382 ppm calibration solution, 230 mL bottle
- MA753** Hard carrying case for 2 testers



**Replaceable probe**

Replace the probe in a fast and simple way yourself! Just unscrew the plastic ring on the top of the probe and replace the probe with a new one.

**Battery life**

Percentage of battery power remaining will be displayed upon startup.



**Packaging Information**

MW803 MAX and MW804 MAX is supplied in a carton box. Optionally the MA753 hard carrying case can be purchased.

**Ordering Information**

MW803 MAX and MW804 MAX is supplied complete with protective cap, 20 mL pH 4.01 and pH 7.01 sachets of calibration solution, 20 mL 1413 µS/cm calibration solution (MW803 MAX), 20 mL 12880 µS/cm calibration solution (MW804 MAX), batteries and instructions.

